



Panel Weight:	ST SM	P25 & P5	4.45 kg/m
Weight Tolerance			±5%
Ridges (Standard)			125 mm
Ridges (K Version)			100 mm
λ m °C			<0.022
K Watt m °C			0.50
I (ISO 717) Soundproof Index (dB)			25

FINISHING External Face	COATING External Face	TYPE External Face	COLOURS* External Face	* Printed colours are for example only. To ensure proper colour and finishing representation, please contact TECSEDO and request a sample.										
STUCCO														
	5µm Paintable Primer		STANDARD COLOURS	RAL 8014	RAL 9002	RAL 9010								
	25µm Polyester		OTHER COLOURS	RAL 3000	RAL 3005	RAL 5010	RAL 6005	RAL 6009	RAL 7004	RAL 7016	RAL 8017	RAL 9006	RAL 9007	Other RAL colours are available on request, subject to minimum quantities
SMOOTH														
	25µm Polyester			RAL 1013	RAL 7016	RAL 7035	RAL 9002	RAL 9006	RAL 9007	RAL 9010	For other models and colors, please contact us			
INTERNAL FACE	COLOURS		25µm Polyester	RAL 9002 Stucco	RAL 9010 Stucco	RAL 9002 Smooth	RAL 9010 Smooth							